



- NOTES:
1. THIS RESERVOIR IS DESIGNED FOR STATIONARY INSTALLATIONS, ANY MOBILE INSTALLATIONS ARE SUBJECT TO FACTORY REVIEW
 2. DO NOT SHIP THIS UNIT FULL OF OIL (APPLIES TO 50+ GALLON RESERVOIRS)
 3. THIS RESERVOIR IS THOROUGHLY CLEANED, A RUST INHIBITOR APPLIED TO THE INTERIOR, AND PRIME PAINTED GRAY PRIOR TO SHIPMENT. ANY SUBSEQUENT CUTTING OR WELDING ON THE UNIT COULD CAUSE CONTAMINATION AND WILL VOID THE WARRANTY
 4. OPERATING TEMPERATURE IS 180° F MAXIMUM. FOR HIGHER TEMPERATURES CONSULT FACTORY
 5. ALL PORTS ARE PLASTIC PLUGGED AND PROTECTED FOR SHIPPING. LEAVE THESE IN PLACE UNTIL THE UNIT IS FINAL PAINTED OR FINISH ASSEMBLED. IF PAINTED AFTER ASSEMBLY, PLUG AND PROTECT ALL OPENINGS INTO THE RESERVOIR
 6. SHIPPED LOOSE: SIGHT GAGE (ALUMINUM WITH BUNA N SEALS)
FILLER BREATHER (STEEL WITH ZINC TRIVALENT CHROME FINISH)
 7. CUTOUT FOR FILLER BREATHER NOT PROVIDED
 8. RECOMMENDED ASSEMBLY TORQUE: ENDCOVER (15 FT LB), SIGHT GAGE (60 IN LB)

THIS DOCUMENT CONTAINS INFORMATION PROPRIETARY TO LDI Industries, Inc. AND IS FURNISHED UPON THE EXPRESS CONDITION THAT THE INFORMATION CONTAINED HEREIN WILL NOT BE DISCLOSED TO ANY THIRD PARTY OR USED DIRECTLY OR INDIRECTLY IN ANY WAY DETRIMENTAL TO THE INTEREST OF LDI Industries, Inc.

LDI Industries **LDI INDUSTRIES, INC.**
MANITOWOC, WI HUNTLEY, IL

				MATERIAL	STEEL	TOLERANCES		TITLE RES_STYLE_HWT_60GAL_STL_PRIME										
				FINISH	SEE NOTE 3	UNLESS OTHERWISE SPECIFIED		LDI STANDARD PRODUCT										
—	—	—	—	NOM WT (LBS.)	270	() REFERENCE DIMENSIONS		DWG NO./ITEM NO. V5162										
REV	DATE	ECN NO.	BY			SCALE 3/16	DO NOT SCALE DRAWING	DRWN	TLS	DATE 10/15/13	CHKD	—	DATE	—	SHT	—	REV	—