APPENDIX LE-1

OIL GAGE MODIFICATIONS

Modifications are specified below. Standard shield threads are 5/8-27 or 3/4-27. Minimum order quantity may be required.

TOP CAP with MALE PIPE NPTF (dryseal) -1MP = 1/8 inch -2MP = 1/4 inch -3MP = 3/8 inch -4MP = 1/2 inch	TOP CAP, NON VENTED -1NV Up to 100 PSI TOP CAP with REPLACEABLE
TOP CAP with FEMALE PIPE NPTF (dryseal) -1FP = 1/8 inch -2FP = 1/4 inch -3FP = 3/8 inch	40 MICRON FILTER VENT -FV Available for both diameter sizes
TOP CAP with COMPRESSION FITTING STRAIGHT TUBE O.D. TUBE -1T = 1/8 inch -3T = 1/4 inch	ADJUSTABLE BRASS RING(S) FLUID LEVEL INDICATORS -1RNG = One ring -2RNG = Two rings ADJUSTABLE RING LOCATION
TOP CAP with COMPRESSION FITTING 90° TUBE O.D. TUBE -3TA = 1/4 inch -4TA = 5/16 inch	SEAL MATERIALS OTHER THAN BUNA N (STANDARD) -2BU = Butyl -4EP = Ethylene Propylene -3VI = Viton A [®] -5SI = Silicone SIGHT MATERIALS OTHER THAN GAGE GLASS (STANDARD)
TOP CAP with SNAP LID FILLER -1FC	Minimum order quantity may be required -1PC = Polycarbonate METAL GAGE PARTS OTHER THAN BRASS (STANDARD) Minimum order quantity may be required -A = Aluminum

HOW TO ORDER LDI INDUSTRIES OIL GAGES WITH MODIFICATIONS

Specify the catalog number and pipe thread of the gage required. Then simply choose the modifications you need using the order code shown above, separating each with a dash.

If you need a modification not included above ask us about it! We will be happy to quote from your sketch or specifications. EXAMPLE:

<u>G1</u>	<u>05-1</u>	L-4	- <u>1PC-3VI</u>	Viton A [®] Seals
				Polycarb sight Aluminum construction
				—— 1/8 NPTF threads —— Catalog Number G105

Dimensions and specifications are subject to change without notice. Not all items are Made-To-Stock, contact us for availability.



02/14