METERING & SHUT OFF VALVES

FFG SERIES - HEAVY DUTY

The FFG Series is ideal for applications which require fine metering and shut-off. Designed for use with air, oil, water, steam, liquid fuels and most chemicals.

Standard Features:


- Heavy duty brazed construction for added strength and safety
- Precision machined stems and valve bodies provide perfect seat alignment for leak-free shut off
- Carbon steel valves are zinc plated and sealed with black chromate for double corrosion protection
- Stem Taper
 - ∘10.5° (1/4 inch size)
- Stem Pitch
 - -16 threads/inch (1/4 inch size)

Standard Material:

Carbon steel

Temperature and Pressure Ratings:

- Maximum operating pressure 10,000 PSI (68948 kPA) Hydraulic Oil
- Maximum operating pressure 2000 PSI (13790 kPa) Air
- Temperature range -40° F to 500° F (-40° C to 260° C)





FFG Series											
Part No.	Body Material	A Female NPT	B Max (inches)	C (inches)	D (inches)	E (inches)	F (inches)	G (inches)	H Dia (inches)	Orifice Dia. (inches)	cv
FFG2002T	Carbon Steel	1/4	3.50	1.03	2.06	2.50	.88	.38	.62	.22	.66

Performance 200 160 120 80 40 0 12.5 25 37.5 50 FLOW (GPM)

Dimensions and specifications are subject to change without notice. Not all items are Made-To-Stock, contact us for availability.

sales@ldi-industries.com